(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 21 July 2005 (21.07.2005)

PCT

(10) International Publication Number WO 2005/065757 A1

(51) International Patent Classification⁷:

A61M 16/00

(21) International Application Number:

PCT/AU2005/000006

- (22) International Filing Date: 7 January 2005 (07.01.2005)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2004900046


7 January 2004 (07.01.2004) AU

- (71) Applicant (for all designated States except US): RESMED LTD [AU/AU]; 97 Waterloo Road, North Ryde, New South Wales 2113 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): BASSIN, David, John [AU/AU]; c/- ResMed Ltd, 97 Waterloo Road, North Ryde, New South Wales 2113 (AU).

- (74) Agents: BORG, Keith, Joseph et al.; Halford & Co, 1 Market Street, Sydney, New South Wales 2000 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: METHODS FOR PROVIDING EXPIRATORY PRESSURE RELIEF IN POSITIVE AIRWAY PRESSURE THERAPY



(57) Abstract: A method of operating a CPAP apparatus in which the interface pressure is controlled to rapidly drop at the start of expiration by an expiratory relief pressure (ERP) that is independent of instantaneous respiratory flow, following which the pressure rises to an inspiratory level at or shortly before the end of expiration, or at the onset of an expiratory pause, if any. The ERP is an increasing function of the inspiratory pressure. The expiratory pressure follows a template that is a function of the expected expiration time, the magnitude of the template being equal to the ERP. The current estimated proportion of expiration is determined by comparing the expiration time of the breath in progress to low-pass filtered expiratory durations measured for a number of the preceding breaths.

WO 2005/065757 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.